



Vintage Prestige | RBxx90

Field of application. Wood, tiles, metal, glass, plastic, wall, fabric, steel and galvanised steel sheet. For indoor and outdoor use.

Information. Vintage Prestige is a ultra-matt enamel. It is a high-covering product, which strongly adheres to all kinds of surfaces. Its formula is odourless and with low VOC emissions. Vintage Prestige is a washable product. No sanding, no stripping, no primer application required. The application of two coats is recommended.

Instructions. Clean the surface from dirt, dust and grease by means of Clean & Grip VY0500, because these substances could avoid the adhesion of the coating. If old coatings peeled off, sand with 150-180 grit sandpaper. Spread the product on the surface. After 2 hours it is possible to apply a second coat. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust, then apply Vintage Prestige products. RBxx90 can be diluted up to 10% for brush application and up to 15-20% for spray application.

Packaging. 0,5 L - 5 L *

**only RB1490, RB2090, RB2190*

Storage	> 5°C
Painting	> 10°C
Ready to use	
Brush Sponge Roller	
Yield	8-10 m²/L
Mix it well	before use
Tack-free	2 h
Drying time	between the coats 4-6 h
Final drying time	6-8 h
Solid content	60 ± 10 %
Viscosity	14000 ± 1000 cps
Specific weight	1,2 ± 0,2 g/cm³
Gloss level	5

RB1090 *dark cherry*
RB1190 *milkshake*
RB1290 *hazelnut*
RB1390 *vanilla*
RB1490 *coconut*
RB1590 *mintgreen*
RB1690 *aniseed*
RB1790 *juniper*
RB1890 *truffle*
RB1990 *marzipan*
RB2090 *milk*
RB2190 *licorice*
RB2290 *sage*
RB2390 *peach*
RB2490 *caramel*

Watch our tutorials

07/26





Vintage Prestige neutral and white base | RB0NTR RB0SBN

Field of application. Wood, tiles, metal, glass, plastic, wall, fabric, steel and galvanised steel sheet. For indoor and outdoor use.

Information. Vintage Prestige neutral and white base must be pigmented to provide a high-covering effect and a strong adhesion to all kinds of surfaces (like the ready-to-be-applied colors). For coloring RB0NTR e RB0SBN do not exceed the addition of 10% EY---M690 pastes. **No sanding, no stripping, no primer application required.** Vintage Prestige pigmented base is a washable product..

Instructions. Clean the surface from dirt, dust and grease by means of Clean & Grip VY0500, because these substances could avoid the adhesion of the coating. If old coatings peeled off, sand with 150-180 grit sandpaper. Spread the pigmented product on the surface. After 2 hours it is possible to apply a second coat. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust, then apply Vintage Prestige pigmented base. Pigmented RB0NTR e RB0SBN can be diluted up to 10% for brush application and up to 15-20% for spray application.

Packaging. RB0NTR 0,92 kg 4,6 kg RB0SBN 1 kg 5 kg

Storage
> 5°C

Painting
> 10°C

To be pigmented

Brush
Sponge
Roller

Yield
8-10 m²/L

Mix it well
before use

Tack-free
2 h

Drying time
between the coats
4-6 h

Final drying time
6-8 h

Solid content
RB0NTR 45 ± 3 %
RB0SBN 63 ± 3 %

Viscosity
RB0NTR 1,14 ± 0,03 g/cm³
RB0SBN 1,35 ± 0,03 g/cm³

Gloss
5

RB0NTR
neutral base
5 gloss

RB0SBN
white base
5 gloss

Watch our tutorials

07/26