SEAJET THINNER A

Product description

Xylene based thinner.

Product data

Flash point	25°C
VOC (Theoratical)	870 g/l.
Pack sizes	1lt, 5lt
Odour	Typical aromatic odour

Application and use

Type	Thinner for antifouling paints.
Recommended use	Seajet Antifouling, SEAJET 015 UNDERWATER PRIMER, SEAJET 021, SEAJET SEOSIL CLEAR COAT, SEAJET TRIPLE PACK, SEAJET SEOSIL RX, SEAJET SEOSIL RX PRO, SEAJET PELLERCLEAN CLEAR COAT, SEAJET RIBCOAT FINISH.
Thinning	Usually not more than 5% of thinner should be added to Seajet Antifoulings and SEAJET 015 UNDERWATER PRIMER.

General information

Storage

Store the containers in a dry, cool and well ventilated space and away from direct sunlight. Containers must be kept firmly closed. Handle with care.

Transportation

The product should stay in a securely closed container during transport.

Shelf life

Min. 3 years @ 20°C

Disposal

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Additional information

More information can be found on www.seajetpaint.com.

Safety information

Personal Protection advice and additional information can be obtained from the product Safety Data Sheet from Chugoku Paints B.V. which is available on request. The minimum safety precautions in dealing with this paint are:

a. Observe the precautionary notices displayed on the container.

b. Provide adequate ventilation.

c. Avoid skin contact and inhalation of spray mist and vapours.

d. If the product comes into contact with the skin, wash thoroughly with luke warm water and soap or suitable cleaner. If the eyes are contaminated, irrigate with water and seek medical advice immediately.

e. Since the product contains flammable materials, keep away from sparks and open flames. No smoking should be permitted in the area.

Disclaimer

Data, specifications, directions and recommendations given in this data sheet represent test results or experience obtained under controlled or specially defined circumstances.Their accuracy, completeness or appropriateness under the actual conditions of any intended use is not guaranteed and must be determined by user. Product data is subject to change without notice and automatically void two years from issue. All legal relations of Chugoku Paints B.V. will be governed by the Uniform Terms of Sale and Delivery of Chugoku Paints B.V. as last filed with the district court of Rotterdam and upon request they will be made available without charge. Chugoku Paints B.V. explicitly rejects the applicability of any General Conditions, which its contractual parties may use. Exclusive jurisdiction: competent Court in Rotterdam.
Some products have been specially modified to adapt to specific European requirements with regard to European-, national- and local laws and regulations or with regards to specific European use requirements. As a result some physical properties in a TDS may differ from those given in the original Japanese TDS.